



Features

- Contemporary lighting family includes sconce, bollard and path light in new Graphite finish
- Low-VOC painted aluminum housing with polycarbonate lens
- 3000K color temperature with 90+ CRI
- cETLus Listed for wet locations
- 30,000 hours rated life

Available Finishes



Graphite

Listing / Ratings



FRAMEWRX Bloom Series

A gracefully curved light that delivers warm white light in 360 degrees. This large scale design, with up to 720 lumens of light, lends itself to light commercial applications and larger scale residential use. The family casts 3000K warm white LED light for easy integration into residential landscape lighting designs. The bollard has 120-277V AC input and a 39.4" height for commercial applications.

Technical Information

Series	BLOOM
Input Voltage	120-277V AC / 120-277V AC / 12V AC/DC
CCT	3000K (WW)
CRI	90+
Wattage	10W / 10W / 10W
Lumens	up to 720Lm
Beam Angle	120°
Dimmable	N/A
Mounting	Surface Mount
Rating	cETLus Listed (wet location)
Rated Life	30,000 hrs

FRAMEWRX Bloom Series



Bloom Bollard Light
BOL-BLOOM-GT (120-277V / 10W / 720Lm)
 10-1/4"W x 10-1/4"D x 39-13/32"H



Bloom Wall Sconce
SCO-BLOOM-GT (120-277V / 10W / 720Lm)
 10-1/4"W x 12-3/8"D x 10"H



Bloom Path Light
PATH-BLOOM-GT (12V / 10W / 720Lm)
 10-1/4"W x 10-1/4"D x 18"H

PATH-SMS
 Soil mounting stake for FrameWRX path lights

TRULUX LIGHTING SYSTEMS

TASK LIGHTING

DOWNLIGHTING

DECORATIVE LAMPS

BLOOM SERIES
 ARCHITECTURAL LIGHTING

POWER SUPPLIES